2000 ORDERING SUPPLEMENT
MIDDLE EAST

Osmidgpg

REQUIRED ON ALL MIDDLE EAST ORDERS		
RPO	**DESCRIPTION**	
EXP	Processing Option: GMODC, Export	X
K53	Fuel Sender Assy: Robust Fuel System	X
NM2	Leaded Fuel Provisions	X
R6K	Processing Option: Middle East	X
T62	Daytime Running Lights Delete	X
UC2	Speedometer: Kilo/Miles, Kilo Odometer, Positive Bias	X
UD4	Speed Warning Device	X
UL0	Radio: AM/FM Stereo, Seek/Scan, Cassette, Clock, ETR	X
UL2	Radio Frequency: Europe	X
V87	Vehicle Certification Label	X
VC5	Shipping Label	X
VK3	Front License Plate Bracket	X
VPH	Export Vehicle Preparation – Includes (BAG) Export Parts Pkg., (VR6) Tie Down Hook, (V70) Tow Hook	X
Z5X	Mirror: Outside, Rearview, Arabic Language Warning. **Requires** DE2/DE5 Mirrors	X
ZQ2	Convenience Package – Includes (AU3) Power Door Locks, (A31) Power Windows	X

MODEL AND POWERTRAIN AVAILABILITY				
MODEL	**DESCRIPTION**	**ENG.**	**DISPL.**	**TRANS.**
TG21406	Passenger Van (C6P) GVW 8600 lbs	L31	5.7L V8	MT1

EXPORT RESTRICTIONS:	
AJ1	Deep Tinted Glass – **Not Available**
Z82	Trailering, Special Equipment – **Not Available**

SAVANA PASSENGER

2 WHEEL DRIVE	G11406
2 WHEEL DRIVE	G21406
2 WHEEL DRIVE	G21706
2 WHEEL DRIVE	G31406
2 WHEEL DRIVE	G31706

"STEP by STEP"

STEP #1:	SELECT	MODEL CODE Review Standard Equipment
STEP #2:	SELECT	PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE
STEP #3:	SELECT	POWER TEAM REQUIREMENTS
STEP #4:	SELECT	ADDITIONAL OPTIONS
STEP #5:	SELECT	COLOUR, TRIM AND PAINT APPLICATION CODE

2000 LIGHT DUTY TRUCKS

STEP #1: SELECT MODEL CODE – Review Standard Equipment

SAFETY/SECURITY	ZW9	YC6
Airbags: Driver and Passenger	S	S
Brakes: Four wheel antilock system. Power self adjusting	S	S
Child Safety Door Locks: On rear and side loading doors	S	S
Daytime Running Lights	S	S
Passlock™ Security System	S	S
Side Guard Door Beams: Front doors and side cargo door	S	S
Single Two-Sided Key	S	S
EXTERIOR		
Bumpers: Front, painted argent. Rear, painted argent with entry assist step	S	---
Front, chrome with step pad. Rear, chrome with entry assist step	---	S
Corrosion Protection: Two-sided galvanized steel, except roof; 7-stage phosphate bath for entire vehicle; anti-chip coating on lower body area	S	S
Doors: Left hand and right hand front side doors; swing-out, hinged, side cargo doors	S	S
Rear load doors, full opening; hidden hinges; bumper extends beyond opened doors	S	S
Glass: All windows Solar-Ray™ tinted	S	S
Grille: Moulded plastic grille painted dark argent; integral "GMC" letters at centre	S	---
Chrome	---	S
Headlamps, Halogen: Single rectangular sealed beam; hi/low beam	S	---
Dual composite; hi/low beam	---	S
Horns, Dual	S	S
Lights: Backup Lamps; Combination Parking/Direction/Hazard; Combination Tail/Stop/Direction/Hazard; Headlamps; License Plate Lamp; Side Marker Lamps with Reflectors; Centre High Mounted Stop Lamp.	S	S
Mirrors: Left hand and right hand manual control, black, fold-away	S	S
Mouldings: Body side, graphite	---	S
Spare Tire Carrier: Winch-type; under body at rear, behind axle	S	S
Wheels: Argent wheel with black plastic centre cap	S	---
Argent wheel with bright trim rings and chromed centre caps	---	S
Windshield Wipers and Washers: Intermittent wiper system, wet-arm washer system	S	S
INTERIOR		
Air Conditioning, Front	S	S
Armrests: Left hand and right hand side doors; padded	S	S
Assist Handle: Front passenger side	S	S
Coat Hooks, 3: One hook in centre area behind driver; left and right hooks in rear area	S	S
Convenience Groups: Power windows and power door locks	---	S
Tilt wheel and speed control	---	S
Cup Holders: Two, in instrument panel	S	S
Floor Covering: Full width embossed black vinyl, front and rear	S	---
Full length carpet with Scotchgard™; front and rear colour-keyed rubber mats	---	S
Headliner: Cloth above driver and passenger seats, ful length	S	S
Headlamps On Warning Alarm	S	S
Heater and Defogger: Outside air heater with windshield and side window defoggers	S	S
Instruments, Gauges: Speedometer, Odometer, Fuel, Voltmeter, Temperature, Oil Pressure and Trip Odometer	S	S
Lighter, Cigarette	S	S
Lights: Front, centre and rear dome lamps with door-actuated switches	S	S
Reading lamps, stepwell lamps, underhood lamp.	---	S
Parcel Tray: On top surface of instrument panel extension (with L29 or L65 only)	S	S
Power Outlet, Auxiliary: one covered auxiliary power outlet on instrument panel	S	S
Radio Equipment: Electronically Tuned AM/FM Stereo Radio with Seek-Scan and Digital Clock	S	---
Electronically Tuned AM/FM Stereo Radio with Auto Reverse Music Search Cassette Player, Automatic Tone Control, Digital Clock, Seek-Scan and Power Antenna	---	S
Seats: Reclining high back bucket driver and front passenger seats, with integral head restraints and map pockets; assist handle on back of passenger seat	S	S
Vinyl trim	S	---
Custom cloth trim with Scotchgard™ and inboard armrests on seats	---	S
Two 3-passenger bench seats (G11406)	S	S
Two 3-passenger bench seats; one 4-passenger rear bench seat (G21406, G21706, G31406, G31706)	S	S
Steering Wheel and Column: Black energy-absorbing steering column, black vinyl wheel	S	S
Stowage Box: In instrument panel extension, lighted	S	S
Sunshades: Colour-keyed cloth; right hand sunshade has full map strap	S	S
Tools: Scissor-type jack and wheel wrench. Located at right rear of vehicle	S	S
Trim Panels: Composite panels	S	---
Composite with cloth inserts in rear panels	---	S

S Standard

STEP #2: SELECT PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE

REFER TO GENERAL INFORMATION SECTION FOR HOW TO ORDER INFORMATION WHEN CHANGING POWERTRAIN

NOTE: SEE POWER TEAM CHARTS FOR CORRECT UPGRADES COMPATIBILITY

OPTION DESCRIPTION	OPTION CODE	SELECT-A-UNIT CODES 1	2	3	4
PREFERRED EQUIPMENT GROUP	--	1SA	1SB	1SC	1SD
BODY CODE: SL	ZW9	X	X	X	X
Engine: Vortec 4300 SFI V6 (G11406)	L35	U	U	U	U
Engine: Vortec 5700 SFI V8 (G21406, G31406, G31706)	L31	U	U	U	U
Engine: Vortec 5700 SFI V8 (G21706)	L31	X	X	X	X
Transmission: 4-Speed Automatic with Overdrive (G11406)	M30	X	X	X	X
Transmission: 4-Speed Automatic with Overdrive (G21406, G21706, G31406, G31706)	MT1	X	X	X	X
GVWR: 3220 kgs (7100 lbs) (G11406)	C5Y	X	X	X	X
GVWR: 3901 kgs (8600 lbs) (G21406, G21706)	C6P	X	X	X	X
GVWR: 4309 kgs (9500 lbs) (G31406, G31706)	E23	X	X	X	X
Axle, Rear: 3.42 Ratio (G11406)	GU6	U	U	U	U
Axle, Rear: 3.73 Ratio (G21406, G21706, G31406, G31706)	GT4	U	U	U	U
Tires: P235/75R-15/X All Season SBR Blackwall (G11406)	YHA	U	U	U	U
Tires: LT225/75R-16/E All Season SBR Blackwall (G21406, G21706)	YHF	X	X	X	X
Tires: LT245/75R-16/E All Season SBR Blackwall (G31406, G31706)	YHH	X	X	X	X
Seating: Eight Person (G11406)	ZP8	U	U	U	U
Seating: Twelve Person (G21406, G31406, G31706)	ZX5	U	U	U	U
Seating: Twelve Person (G21706)	ZX5	X	X	X	X
Convenience Group: Power Windows and Power Door Locks	ZQ2		X	S	S
Convenience Group: Tilt Wheel and Speed Control	ZQ3		X	S	S
Lighting, Auxiliary: Reading lamps, underhood lamp, stepwell lights on front and side doors	TR9		X	S	S
Model Option: SLE	YC6			X	X
Air Conditioning: Front and Rear	C69				X
Glass: Deep Tint	AJ1				X
Mirrors, Exterior: Left and Right Electric Remote Control, Folding	DE5				X
Mirrors, Interior: Left and Right Sunshade, Illuminated	DH6				X
Remote Keyless Entry	AU0				X
Steering Wheel: Leather Wrapped	NP5				X
Wheels: Aluminum (G11406)	N90				U

X **Option Included in Select-A-Unit DO NOT DELETE**
U **Option Included in Select-A-Unit and May Be Deleted if Substitute Option is Specified**
S **Standard**

2000 LIGHT DUTY TRUCKS

STEP #2: SELECT PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE

Description	Model Code	Model Option	Select-A-Unit Code	Option Code
2 WHEEL DRIVE – 1500 SERIES – 135 INCH WHEELBASE				
SL				
Model Price	**G11406**	**ZW9**	**1**	**1SA**
Preferred Equipment Group Price	G11406	ZW9	2	1SB
SLE				
Model Price	**G11406**	**YC6**	**3**	**1SC**
Preferred Equipment Group Price	G11406	YC6	4	1SD
2 WHEEL DRIVE – 2500 SERIES – 135 INCH WHEELBASE				
SL				
Model Price	**G21406**	**ZW9**	**1**	**1SA**
Preferred Equipment Group Price	G21406	ZW9	2	1SB
SLE				
Model Price	**G21406**	**YC6**	**3**	**1SC**
Preferred Equipment Group Price	G21406	YC6	4	1SD
2 WHEEL DRIVE – 2500 SERIES – 155 INCH WHEELBASE				
SL				
Model Price	**G21706**	**ZW9**	**1**	**1SA**
Preferred Equipment Group Price	G21706	ZW9	2	1SB
SLE				
Model Price	**G21706**	**YC6**	**3**	**1SC**
Preferred Equipment Group Price	G21706	YC6	4	1SD
2 WHEEL DRIVE – 3500 SERIES – 135 INCH WHEELBASE				
SL				
Model Price	**G31406**	**ZW9**	**1**	**1SA**
Preferred Equipment Group Price	G31406	ZW9	2	1SB
SLE				
Model Price	**G31406**	**YC6**	**3**	**1SC**
Preferred Equipment Group Price	G31406	YC6	4	1SD
2 WHEEL DRIVE – 3500 SERIES – 155 INCH WHEELBASE				
SL				
Model Price	**G31706**	**ZW9**	**1**	**1SA**
Preferred Equipment Group Price	G31706	ZW9	2	1SB
SLE				
Model Price	**G31706**	**YC6**	**3**	**1SC**
Preferred Equipment Group Price	G31706	YC6	4	1SD

STEP #3: SELECT POWER TEAM REQUIREMENTS

Engine, Transmission, Axle Ratio and GVWR Code Must Be Specified

G11406

					GVWR Code	C5Y	
					kgs	3220	
					lbs	7100	
					Axle Ratio	3.42	3.73
Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type		Axle Ratio Codes	
L35 V6	4.3 Litre	SFI	200 @ 4400	M30-Automatic w/Overdrive		GU6	GT4
L30 V8	5.0 Litre	SFI	220 @ 4600	M30-Automatic w/Overdrive		GU6	---
L31 V8	5.7 Litre	SFI	245 @ 4600	M30-Automatic w/Overdrive		GU6	GT4

G21406, G21706

					GVWR Code	C6P	
					kgs	3901	
					lbs	8600	
					Axle Ratio	3.73	4.10
Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type		Axle Ratio Codes	
L31 V8	5.7 Litre	SFI	250 @ 4600	MT1-Automatic w/Overdrive		GT4	GT5
* L65 V8	6.5 Litre 395 Cu. In.	Turbo Diesel	195 @ 3400	MT1-Automatic w/Overdrive		GT4	GT5

* **L65 is Not Available on G21706.**

G31406, G31706

					GVWR Code	E23		
					kgs	4309		
					lbs	9500		
					Axle Ratio	3.42	3.73	4.10
Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type		Axle Ratio Codes		
L31 V8	5.7 Litre	SFI	250 @ 4600	MT1-Automatic w/Overdrive		---	GT4	GT5
L29 V8	7.4 Litre	SFI	290 @ 4000	MT1-Automatic w/Overdrive		* GU6	GT4	GT5
L65 V8	6.5 Litre 395 Cu. In.	Turbo Diesel	195 @ 3400	MT1-Automatic w/Overdrive		---	GT4	GT5

* **Not Available with G80**

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code
ENGINES: – Refer to Power Teams Chart for compatibility.	
Vortec 4300 Sequential Fuel Injection (SFI) V6	L35
Vortec 5000 Sequential Fuel Injection (SFI) V8	L30
Vortec 5700 Sequential Fuel Injection (SFI) V8. With MT1 includes an auxiliary transmission oil cooler.	
Optional with: G11406	L31
G21406, G21706, G31406, G31706	L31
Vortec 7400 Sequential Fuel Injection (SFI) V8	L29
6.5 Litre (395 Cu. In.) Turbo Diesel V8. Includes an auxiliary engine oil cooler and an auxiliary transmission oil cooler. Includes dual batteries – one is on frame rail behind driver's door, the other is in right hand corner under hood.	
Optional with: G21406, G31406, G31706	L65
Alternative Fuel Compatible Engine:	
Provides only the engine with internal modifications for operation with natural or propane gas. **Requires** L31 and MT1. **Not available** G11406.	KL5
TRANSMISSION: – Refer to Power Teams Chart for compatibility	
4-Speed Electronic Automatic with Overdrive	M30
4-Speed Electronic Automatic with Overdrive	MT1
GVWR: – Refer to Power Teams Chart for compatibility	
3220 kgs (7100 lbs)	
Optional with: G11406	C5Y
3901 kgs (8600 lbs)	
Optional with: G21406, G21706	C6P
4309 kgs (9500 lbs). Includes an auxiliary transmission oil cooler.	
Optional with: G31406, G31706	E23
AXLES, REAR: – Refer to Power Teams Chart for compatibility	
Ratio Codes 3.42	GU6
3.73	GT4
4.10	GT5
Locking Differential. **Not available** with GU6 on G31406 or G31706	G80
TIRES:	
P235/75R-15/X All Season Steel Belted Radial Blackwall. Front, Rear and Spare.	
Optional with: G11406	YHA
P235/75R-15/X All Season Steel Belted Radial White Stripe. Front, Rear and Spare.	
Optional with: G11406	YHB
P235/75R-15/XL All Season Steel Belted Radial White Outline Lettered. Front, Rear and Spare.	
Optional with: G11406	YHM
LT225/75R-16/E All Season Steel Belted Radial Blackwall. Front, Rear and Spare.	
Optional with: G21406, G21706	YHF
LT245/75R-16/E All Season Steel Belted Radial Blackwall. Front, Rear and Spare.	
Optional with: G31406, G31706	YHH
Spare Tire Delete. Deletes Spare Tire, Wheel and Jack.	
Optional with: with YHA on G11406	ZX9
with YHB on G11406	ZX9
with YHM on G11406	ZX9
with YHF on G21406, G21706	ZX9
with YHH on G31406, G31706	ZX9
SEATING ARRANGEMENTS:	
Eight Person Seating. Includes two front high back bucket seats and two rear 3-passenger bench seats.	
Optional with: 'W' or 'G' Trim on G11406	ZP8
'W' or 'G' Trim on G21406, G31406	ZP8
Five Person Seating. Includes two front high back bucket seats and one rear 3-passenger bench seat.	
Optional with: 'W' or 'G' Trim on G11406	ZP5
Twelve Person Seating. Includes two front high back bucket seats, two 3-passenger bench seats and one 4-passenger rear bench seat.	
Optional with: 'W' or 'G' Trim on G21406, G21706, G31406, G31706	ZX5
Fifteen Person Seating. Includes two front high back bucket seats, three 3-passenger bench seats and one 4-passenger rear bench seat.	
Optional with: 'W' or 'G' Trim on G31706	ZP3

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code

AIR CONDITIONING: Front and Rear.
Includes KW2, C36 and rear overhead mounted recirculating air system.
Optional with: ..... SAU 1 or SAU 2 on G11406 ..... C69
..... SAU 3 on G11406 ..... C69
..... SAU 1 or SAU 2 on G21406, G21706, G31406, G31706 ..... C69
..... SAU 3 on G21406, G21706, G31406, G31706 ..... C69

ALTERNATOR, 124 AMP:
Included with C69. Included on G21406, G21706, G31406, G31706.
Optional with: ..... G11406 ..... KW2

COLD CLIMATE PROVISION: **Includes** engine block heater. **Not Available** L65. ..... V10

CONVENIENCE GROUPS:
Power Windows and Power Door Locks.
Optional with: ..... SAU 1 ..... ZQ2
Tilt Wheel and Speed Control.
Optional with: ..... SAU 1 ..... ZQ3

DOOR: Sliding Side Rear.
Includes Child Safety Door Lock. Please note swing out side is standard. YA2

FLOOR COVERING, CARPET: Full length carpeted floor covering.
Includes colour-keyed vinyl front and rear mats. Included with YC6.
Optional with: ..... SAU 1, 2 ..... B30

GLASS, DEEP TINT: Optional with: ..... SAU 1, 2, 3 ..... AJ1

HEATER: Rear.
Located on left side rear corner behind rear wheelhouse. Included with C69.
Optional with: C36

LIGHTING, AUXILIARY:
Includes reading lamps, stepwell lamps on front and side doors, underhood lamp.
Optional with: ..... SAU 1 ..... TR9

MIRRORS, EXTERIOR:
Left hand and right hand electronic remote control, with defog feature; folding.
With SAU 1 **Requires** ZQ2.
Optional with: ..... SAU 1, 2, 3 ..... DE5

MIRRORS, INTERIOR: Sunshade. Left and right illuminated.
Optional with: ..... SAU 3 ..... DH6

PAINT SCHEME: Solid. See Colour, Trim and Seat Availability Chart. ZY1

RADIO EQUIPMENT:
Antenna, Power. Included with YC6, UL0, UN0, UP0.
Optional with: ..... SAU 1 or SAU 2 with UL0, UN0, UP0 ..... U75
..... SAU 1 or SAU 2 less UL0, UN0, UP0 ..... U75
Electronically Tuned AM/FM Stereo Radio with Seek-Scan, Stereo Cassette Tape and Digital Clock. Includes fixed mast antenna, premium dual front and rear speakers.
Optional with: ..... SAU 1, 2 ..... UM6
Electronically Tuned AM /FM Stereo Radio with Auto Reverse Music Search Cassette, Automatic Tone Control, Digital Clock, Seek-Scan, 4 front and rear speakers. Includes U75. With SAU 1 **Requires** ZQ2. Included with YC6.
Optional with: ..... SAU 1, 2 ..... UL0
Electronically Tuned AM/FM Stereo Radio with Compact Disc Player, Automatic Tone Control, Digital Clock, Seek-Scan, 4 front and rear speakers. Includes U75. With SAU 1 **Requires** ZQ2.
Optional with: ..... SAU 1, 2 ..... UN0
..... SAU 3, 4 ..... UN0
Electronically Tuned AM/FM Stereo Radio with Seek-Scan, Auto Reverse Music Search Cassette, Compact Disc Player, Automatic Tone Control and Digital Clock, 4 front and rear speakers. Includes U75. With SAU 1 **Requires** ZQ2.
Optional with: ..... SAU 1, 2 ..... UP0
..... SAU 3, 4 ..... UP0

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code
REMOTE KEYLESS ENTRY:	
Optional with: ..... SAU 3	AU0
SEAT ADJUSTER:	
Driver, 6-way power. **Requires** 'G' trim code	AG1
Passenger, 6-way power. **Requires** AG1 and 'G' trim code	AG2
STEERING WHEEL, LEATHER WRAPPED:	
Optional with: ..... SAU 1, 2 or 3	NP5
TRAILERING, SPECIAL EQUIPMENT:	
Heavy Duty. Includes Weight Distributing Platform Type Trailer Hitch and 8-lead type wiring harness with heavy duty flasher. Additional cooling not required	Z82
WHEEL TRIM: Bright trim rings with bright centre caps. **Not Available** with or N90	
Optional with: ..... SAU 1, 2	P06
WHEELS:	
Aluminum.	
Spare is a steel wheel. Included with SAU 4.	
Optional with: ..... SAU 1 or 2 on G11406	N90
..... SAU 3 on G11406	N90

DESCRIPTION	Order Code	Lead Time Days

SPECIAL EQUIPMENT WHEN INSTALLED AT ASSEMBLY PLANT

PAINTS: Solid. **Requires** 01U Colour Code One.		
Green, Woodland	9V5	--
Tan, Doeskin	9V9	--
Yellow, Wheatland	9W3	--
Orange, Tangier	9W4	--

STEP #5: SELECT COLOUR, TRIM AND PAINT APPLICATION CODE

ZY1 PAINT APPLICATION

	Seat Ordering Information			Interior Trim		
Body Code	Type	Seat Material	Option Code	Navy	Neutral	Medium Gray
ZW9	High Back Bucket	Vinyl	§ ZP8 / ZX5	26W	52W	92W
(SAU 1, 2)	High Back Bucket	Custom Cloth	§ ZP8 / ZX5	26G	52G	92G
ZW9 (SAU 3, 4)	High Back Bucket	Custom Cloth	§ ZP8 / ZX5	26G	52G	92G

Exterior Paint Colour	Code	Available Combinations		
Medium Strom Gray (Met)	14U	X	---	X
Fernmist Green (Met)	31U	---	X	X
Indigo Blue (Met)	39U	X	X	X
Black	41U	---	X	X
Summit White	50U	X	X	X
Dark Carmine Red (Met)	51U	---	X	X
Light Autumnwood (Met)	55U	---	X	---
Fire Red	74U	---	X	X
Dark Bronzemist (Met)	76U	---	X	X

§ **Seat option may be changed, check SEATING ARRANGEMENTS.**

DATE: February 14, 2000
REVISION NO: 00-3

GENERAL MOTORS OVERSEAS DISTRIBUTION CORPORATION

2000

UPDATE

GMC

SAVANA PASSENGER

TRUCK TECHNICAL PAGES

Attached is revision 00-3 of the Light Duty Truck Technical Pages.

The information contained in the Technical Pages is confidential and should not be disclosed to unauthorized persons or used for non-business purposes.

MODEL SELECTION SUMMARY

SERIES	MODEL NUMBER/ BODY CODE/ OPTION CODE	PASSENGER CAPACITY (STD/OPT)	STANDARD ENGINE/ TRANS	OPTIONAL ENGINE/ TRANS	GVWR KG (LB)	GAWR KG (LB) FRONT/ REAR	MAXIMUM PAYLOAD KG (LB)	MAX GROSS TRAILER WT/ TONGUE LOAD KG (LB)
SAVANA PASSENGER								
G10 REGULAR WHEELBASE	CG11406/ ZW9	8/5	4300 V6/A4	— 5000 V8/A4 5700 V8/A4	3220 (7100)	1633/1780 (3600/3968)	866 (1911)	2449/* (5400) 2631/* (5800) 3311/* (7300)
G20 REGULAR WHEELBASE	CG21406/ ZW9	12/8	5700 V8/A4	— 6.5L V8/A4	3901 (8600)	1724/2431 (3800/5360)	1239 (2732)	3765/* (8300) 4037/* (8900)
G20 EXTENDED WHEELBASE	CG21706/ ZW9	12/–	5700 V8/A4	—	3901 (8600)	1860/2431 (4100/5360)	1144 (2523)	3765/* (8300)
G30 REGULAR WHEELBASE	CG31406/ ZW9	12/8	5700 V8/A4	— 7400 V8/A4 6.5L V8/A4	4309 (9500)	1950/2760 (4300/6084)	1584 (3494)	3674/* (8100) 4536/* (10000) 3992/* (8800)
G30 EXTENDED WHEELBASE	CG31706/ ZW9	12/15	5700 V8/A4	— 7400 V8/A4 6.5L V8/A4	4309 (9500)	1950/2760 (4300/6084)	1488 (3281)	3674/* (8100) 4536/* (10000) 3992/* (8800)

*Trailer tongue weight should be 10 to 15% of total loaded trailer weight. (up to 1000 lbs).

POWERTRAINS

ENGINES

	VORTEC 4300 V6	VORTEC 5000 V8	VORTEC 5700 V8	VORTEC 7400 V8 HD	6.5L V8 TURBO DIESEL HD	
Order Code	L35 (Standard w/G11406)	L30	L31	L29	L65	R
Availability	G11406	G11406	All	G31406/ G31706	G21406/ G31406/ G31706	R R R
SAE Net Kilowatts @ rpm (Horsepower @ rpm)	149 @ 4400 (200@ 4400)	164 @ 4600 (220 @ 4600)	190 @ 4600 (255 @ 4600)	216 @ 4000 (290 @ 4000)	145 @ 3400 (195 @ 3400)	R R
SAE Net Torque N-m @ rpm (lb-ft @ rpm)	339 @ 2800 (250 @ 2800)	379 @ 2800 (280 @ 2800)	447@ 2800 (330 @ 2800)	556 @ 3200 (410 @ 3200)	583 @ 1800 (430 @ 1800)	R R
Fuel System	SFI	SFI	SFI	SFI	Indirect Fuel Injection	R R
Standard Delco Freedom Battery (12 volt negative ground) Cold Cranking Amps @ -17.8° C (0°F)	600	600	600	600	2 @ 600 each	R
Standard Delcotron Alternator Maximum Capacity Amps	100	100	100	124	124	R

TRANSMISSIONS

	ELECTRONIC AUTOMATIC 4-SPEED OVERDRIVE W/TORQUE CONVERTER CLUTCH (4L60-E) (Includes brake/transmission shift interlock)	ELECTRONICALLY CONTROLLED AUTOMATIC 4-SPEED W/OD HEAVY DUTY (4L80-E) (Includes brake/transmission shift interlock)
Order Code	M30 (Standard w/C5Y)	MT1 (Standard w/C6P;E23)
Application	L35/L30/L31	L31 HD/L29/L65
Gear Ratios		
First	3.06	2.48
Second	1.63	1.48
Third	1.00	1.00
Fourth	0.70	0.75
Reverse	2.29	2.08
Power Take-Off	No	No

REAR AXLES

Availability	G11406		G21406 w/o L65 and G21706		G21406 w/L65; G31406/G31706		
Make	GM		GM		GM		
Capacity kg (lb)	1814 (4000)		2585 (5700)		2760 (6084)		
Type	Semi-Floating		Full-Floating		Full-Floating		
Pinion and Ring Gear Type	Hypoid		Hypoid		Hypoid		
Engine Availability[1]	L35 L30 L31	L35 L31	L31	L31	L29	L29/ L31/ L65	L29/ L31/ L65
Axle Ratio Code	GU6 (Standard)	GT4	GT4 (Standard)	GT5	GU6	GT4[2]	GT5
Ratio	3.42	3.73	3.73	4.10	3.42	3.73	4.10
Pinion Teeth	12	11	11	10	12	11	10
Ring Gear Teeth	41	41	41	41	41	41	41
Ring Gear Diameter (in.)	8.6	8.6	9.5	9.5	10.5	10.5	10.5

Note: Axle ratio availability depends on model, powertrain and emissions selected.
[1]Engine applications are heavy duty (HD) at 3901 kg (8600 lb) GVWR or above.
[2]Standard axle on G31406 and G31706.

BRAKES

Type	Power Self-Adjusting 4-Wheel Anti-Lock	Power Self-Adjusting 4-Wheel Anti-Lock	Power Self-Adjusting 4-Wheel Anti-Lock
Application	G11406	G21406 w/o L65; G21706	G21406 w/L65; G31406/G31706
Front Rotor Size mm (in.)	Disc 294 x 32 (11.57 x 1.25)	Disc 318 x 32 (12.5 x 1.26)	Disc 318 x 32 (12.5 x 1.26)
Rear Size mm (in.)	Drum 283 x 70 (11.15 x 2.75)	Drum 330 x 63.5 (13 x 2.5)	Drum 330 x 88.9 (13 x 3.5)
Booster Type	Vacuum	Hydraulic	Hydraulic
Parking Brake Type Operation	Cable to Rear Wheels Pedal	Cable to Rear Wheels Pedal	Cable to Rear Wheels Pedal

TIRES

KEY: ALS = ALL-SEASON SBR = STEEL-BELTED RADIAL PLY BW = BLACKWALL WS = WHITE STRIPE WOL = WHITE OUTLINE LETTERED

TIRE DESCRIPTION		FRONT/REAR/SPARE
P235/75R15X	ALS/SBR/BW	YHA (Standard G11406)
P235/75R15X	ALS/SBR/WS	YHB
P235/75R15	ALS/SBR/WOL	YHM
LT225/75R16E	ALS/SBR/BW	YHF (Standard G21406/G21706)
LT245/75R16E	ALS/SBR/BW	YHH (Standard G31406/G31706)

STANDARD CHASSIS FEATURES

AIR BAGS	Driver and Passenger
ENGINE BLOCK HEATER	
EXHAUST SYSTEM	
Type	Stainless steel with converter
FRAME	
Type	Full-length, all-welded, ladder-type construction
FUEL TANK	
Location	Forward of rear axle between frame rails
Capacity (approx.)	117 Litres (25.8 imperial gal)
GVWR	
C5Y–G11406	3220 kg (7100 lb)
C6P–C21406/G21706	3901 kg (8600 lb)
E23–G31406/G31706	4309 kg (9500 lb)
STEERING	
Type	Integral Power

SUSPENSION, FRONT	Independent
Capacity	
G11406	1633 kg (3600 lb)
G21406/G21706/ G31406/G31706	1950 kg (4300 lb)
Springs	Coil
Capacity	
G11406	816 kg (1800 lb) each
G21406	862 kg (1900 lb) each
G21706	930 kg (2050 lb) each
G31406/G31706	975 kg (2150 lb) each
Shock Absorbers	
G11406	47mm (1.85") piston diameter
G21406/G31406	32mm (1.26") piston diameter
Stabilizer Bar	30mm (1.18") diameter
SUSPENSION, REAR	
Springs	Multi-leaf
G11406	900 kg (1984 lb) each
G21406/G21706	1215 kg (2680 lb) each
G31406/G31706	1380 kg (3042 lb) each
Shock Absorbers	
G11406	36mm (1.41") piston diameter
G21406/G31406	32mm (1.26") piston diameter
WHEELS	
Type	Five disc, painted argent with 4 black plastic centre caps
Size	
G11406	381mm x 178mm (15" x 7")
G21406/G21706/ G31406/G31706	406mm x 165mm (16" x 6.5")
Attachment	
G11406	5 bolts on 127mm (5") circle
G21406/G21706/ G31406/G31706	8 bolts on 165mm (6.5") circle

DIMENSIONS

SERIES	**G10**	**G20**		**G30**	
MODEL	**REGULAR WHEELBASE**	**REGULAR WHEELBASE**	**EXTENDED WHEELBASE**	**REGULAR WHEELBASE**	**EXTENDED WHEELBASE**
MODEL NUMBER	**G11406/ZW9**	**G21406/ZW9**	**G21706/ZW9**	**G31406/ZW9**	**G31706/ZW9**
EXTERIOR DIMENSIONS					
BODY Wheelbase mm (in.)	3429 (135.0)	3429 (135.0)	3937 (155.0)	3429 (135.0)	3937 (155.0)
Overall Length mm (in.)	5555 (218.7)	5555 (218.7)	6063 (238.7)	5555 (218.7)	6063 (238.7)
Overall Height Nominal mm (in.)	2022 (79.6)	2096 (82.5)	2060 (81.1)	2131 (83.9)	2096 (82.5)
Maximum Width mm (in.)	2017 (79.4)	2012 (79.2)	2012 (79.2)	2017 (79.4)	2012 (79.2)
Bumper to Axle					
Front mm (in.)	859 (33.8)	859 (33.8)	859 (33.8)	859 (33.8)	859 (33.8)
Rear mm (in.)	1267 (49.9)	1267 (49.9)	1267 (49.9)	1267 (49.9)	1267 (49.9)
Ground to Top of Rear Load Floor mm (in.)	617 (24.3)	696 (27.4)	704 (27.7)	737 (29.0)	737 (29.0)
Ground Clearance Front/Rear mm (in.)	188(7.4)/183 (7.2)	208 (8.2)/203 (8.0)	206 (8.1)/203 (8.0)	221 (8.7)/216 (8.5)	221 (8.7)/216 (8.5)
Side Load Door Sliding (YA2)					
Opening Height mm (in.)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)
Opening Width mm (in.)	1036 (40.8)	1036 (40.8)	1036 (40.8)	1036 (40.8)	1036 (40.8)
Side Load Door Swing-Out (E24)					
Opening Height mm (in.)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)
Opening Width (in.) —Both Doors Open	1186 (46.7)	1186 (46.7)	1186 (46.7)	1186 (46.7)	1186 (46.7)

DIMENSIONS (CONT'D)

SERIES	G10	G20		G30	
MODEL	REGULAR WHEELBASE	REGULAR WHEELBASE	EXTENDED WHEELBASE	REGULAR WHEELBASE	EXTENDED WHEELBASE
MODEL NUMBER	G11406/ZW9	G21406/ZW9	G21706/ZW9	G31406/ZW9	G31706/ZW9
EXTERIOR DIMENSIONS (CONT'D)					
Rear Load Door					
Opening Height mm (in.)	1242 (48.9)	1242 (48.9)	1242 (48.9)	1242 (48.9)	1242 (48.9)
Opening Width mm (in.)	1445 (56.9)	1445 (56.9)	1445 (56.9)	1445 (56.9)	1445 (56.9)
Turning Diameter Curb-to-Curb m (ft)	13.8 (45.2)	14.4 (47.4)	16.2 (53.4)	14.4 (47.5)	16.3 (53.5)
STEP-UP HEIGHT mm (in.)					
Front Door	434 (17.1)	483 (19.0)	483 (19.0)	521 (20.5)	523 (20.6)
Second Door	394 (15.5)	457 (18.0)	457 (18.0)	495 (19.5)	498 (19.6)
INTERIOR DIMENSIONS					
Headroom mm (in.)					
Front	1031 (40.6)	1031 (40.6)	1031 (40.6)	1031 (40.6)	1031 (40.6)
Second	991 (39.0)	991 (39.0)	991 (39.0)	991 (39.0)	991 (39.0)
Third	993 (39.1)	993 (39.1)	993 (39.1)	993 (39.1)	993 (39.1)
Legroom mm (in.)					
Front	1044 (41.1)	1044 (41.1)	1044 (41.1)	1044 (41.1)	1044 (41.1)
Second	978 (38.5)	978 (38.5)	978 (38.5)	978 (38.5)	978 (38.5)
Third	980 (38.6)	980 (38.6)	980 (38.6)	980 (38.6)	980 (38.6)
Shoulder Room mm (in.)					
Front	1748 (68.8)	1748 (68.8)	1748 (68.8)	1748 (68.8)	1748 (68.8)
Second	1463 (57.6)	1463 (57.6)	1463 (57.6)	1463 (57.6)	1463 (57.6)
Third	1459 (57.4)	1459 (57.4)	1459 (57.4)	1459 (57.4)	1459 (57.4)
Hip Room mm (in.)					
Front	1621 (63.8)	1621 (63.8)	1621 (63.8)	1621 (63.8)	1621 (63.8)
Second	1410 (55.5)	1410 (55.5)	1410 (55.5)	1410 (55.5)	1410 (55.5)
Third	1425 (56.1)	1427 (56.2)	1410 (55.5)	1425 (56.1)	1410 (55.5)
Load Floor Length mm (in.)					
w/Front Seats	3233 (127.3)	3233 (127.3)	3741 (147.3)	3233 (127.3)	3741 (147.3)
w/Front, Middle 1	2238 (88.0)	2238 (88.0)	2746 (108.0)	2238 (88.0)	2746 (108.0)
w/Front, Middle 1, Middle 2	1425 (56.0)	1425 (56.0)	1933 (76.0)	1425 (56.0)	1933 (76.0)
Inside Width @ Beltline mm (in.)	1917 (75.5)	1917 (75.5)	1917 (75.5)	1917 (75.5)	1917 (75.5)
Inside Width Between Wheelhousings mm (in.)	1336 (52.6)	1336 (52.6)	1334 (52.5)	1336 (52.6)	1334 (52.5)
Interior Height mm (in.)	1367 (53.8)	1367 (53.8)	1367 (53.8)	1367 (53.8)	1367 (53.8)
Cargo Volume w/Front Seat litres (cu ft)	6789 (267.3)	6789 (267.3)	8047 (316.8)	6789 (267.3)	8047 (316.8)